

HAMPTON STANDARD OPTIONS


- 9'-0" FIRST FLOOR CEILING HEIGHT
- DIRECT VENT FIREPLACE
- QUOIN CORNERS
- 8/12 PITCH HIP ROOF
- SCHROCK RAISED PANEL OAK CABINETS
- 42" WALL CABINETS
- TRAY CEILING IN MASTER BEDROOM
- COVERED REAR PORCH
- 3RD CAR GARAGE
- LEVEL 2 BETTER CARPET AND PAD



REAR ELEVATION



FRONT ELEVATION



FLOOR PLAN

TOTAL LIVING SQ.FT.	2,620
GARAGE	890
TOTAL SQ.FT.	3,510
EXCLUDING PORCH	62
EXCLUDING PORCH	208

ANDERSEN WINDOW SCHEDULE - 200 SERIES - (1-19)

ANDERSEN MODEL NO.	R.O. SIZE
3030	36" x 36"
3040	36" x 48"
3049*	36" x 51"
3056*	36" x 66"
3060*	36" x 72"
3049 MULL*	73" x 51"
3056 MULL*	73" x 66"
3060 MULL*	73" x 72"
244CT24	28" x 17 1/8"
CTC3	72 3/8" x 38 3/4"

ANDERSEN SLIDING DOOR
R.O. 72 3/4" x 82 1/8"

3'-0" FRONT DOOR
R.O. 38 3/8" x 82 1/2"

3'-0" FRONT DOOR WITH (1) SIDELITE
R.O. 51 7/8" x 82 1/2"

3'-0" FRONT DOOR WITH (2) SIDELITES
R.O. 65 3/8" x 82 1/2"

3'-0" FRONT DOOR - (2) SIDELITES W/ TRANSOM
R.O. 65 3/8" x 96"

R.O. FOR BI-FOLD DOORS USING DRYWALL JAMB FACING = 1 1/4" + DOOR SIZE x (81 1/2")

R.O. FOR BYPASS DOORS USING DRYWALL JAMB FACING MAKE SAME AS BOTH DOORS ADDED TOGETHER

ALL INTERIOR DOORS
SIZE + 2" TO WIDTH x 82 1/2" HIGH

R.O. POCKET DOOR
(2x DOOR WIDTH + 1") x 85" HIGH

* - DENOTES OPENING MEETS EGRESS REQUIREMENTS

9'-0" FIRST FLOOR CEILING HEIGHT

INCLUDES:	
1.	4 1/4" BASEBOARDS IN LIEU OF 3 1/4"
2.	3060 WINDOWS IN LIEU OF 3056 WINDOWS
3.	3056 WINDOWS IN LIEU OF 3049 WINDOWS
4.	DRYWALL WRAPPED OPENINGS 12" TALLER
5.	42" KITCHEN CABINETS STANDARD
6.	16'x8'x8' GARAGE DOORS STANDARD

