





ALL WALL DIMENSIONS ARE FACE TO FACE OF STUDS  
 ALL INTERIOR WALLS ARE 3/2" (UNLESS NOTED)  
 EXHAUST BATH FANS ARE VENTED TO OUTSIDE AIR  
 \*9049 648" (6'7" TO 6" FT. OF CLEAR OPENING)  
 ALL BRICK LAYOUT MEASUREMENTS ARE 4"

4-3  
 (1-35) (1-43) (1-44)  
**FLOOR PLAN**

Total Living Sq.ft.	2103
Garage	524
Total Sq.ft.	2627
Excluding Porch	120

ANDERSEN WINDOW SCHEDULE - 200 SERIES -		
ANDERSEN MODEL NO.	R.O. SIZE	
3030	36" x 36"	
3040	36" x 48"	
3049*	36" x 51"	
3056*	36" x 66"	
3060*	36" x 72"	
3049 MULL*	13" x 51"	
3056 MULL*	13" x 66"	
3060 MULL*	13" x 72"	
ANDERSEN SLIDING DOOR R.O. 12 3/4" x 82 7/8"		
3'-0" FRONT DOOR R.O. 36 3/8" x 82 1/2"		
3'-0" FRONT DOOR WITH (1) SIDELITE R.O. 51 7/8" x 82 1/2"		
3'-0" FRONT DOOR WITH (2) SIDELITES R.O. 65 3/8" x 82 1/2"		
R.O. FOR BI-FOLD DOORS USING DRYWALL JAMB FACING = 1 1/4" + DOOR SIZE x (81 1/2")		
R.O. FOR BYPASS DOORS USING DRYWALL JAMB FACING MAKE SAME AS BOTH DOORS ADDED TOGETHER		
ALL INTERIOR DOORS SIZE + 2" TO WIDTH x 82 1/2" HIGH		
R.O. POCKET DOOR (2x DOOR WIDTH + 1") x 85" HIGH		

\*\* DENOTES OPENING MEETS  
EGRESS REQUIREMENTS